




Olymp



Угол поворота – 180°
Размер светильника:
426×211×262mm
Размер упаковки
светильника:
480×310×152mm
PF ≥ 0,97

○ металл


Артикул	Мощ- ность	Цветовая темпера- тура	Световой поток	Угол рассеи- вания
V1-I0-70077-04L10-6512050	110W	5000K	14850lm	12°
V1-I0-70077-04L02-6512050	110W	5000K	14850lm	30°
V1-I0-70077-04L07-6512050	110W	5000K	14850lm	60°
V1-I0-70077-04L06-6512050	110W	5000K	14850lm	90°
V1-I0-70077-04L08-6512050	110W	5000K	14850lm	30°x110°
V1-I0-70077-04L10-6512040	110W	4000K	14850lm	12°
V1-I0-70077-04L02-6512040	110W	4000K	14850lm	30°
V1-I0-70077-04L07-6512040	110W	4000K	14850lm	60°
V1-I0-70077-04L06-6512040	110W	4000K	14850lm	90°
V1-I0-70077-04L08-6512040	110W	4000K	14850lm	30°x110°
V1-I0-70077-04L10-6512030	110W	3000K	14850lm	12°
V1-I0-70077-04L02-6512030	110W	3000K	14850lm	30°
V1-I0-70077-04L07-6512030	110W	3000K	14850lm	60°
V1-I0-70077-04L06-6512030	110W	3000K	14850lm	90°
V1-I0-70077-04L08-6512030	110W	3000K	14850lm	30°x110°




Угол поворота – 180°
Размер светильника:
546×211×262mm
Размер упаковки
светильника:
595×315×150mm
PF ≥ 0,97

○ металл

Артикул	Мощ- ность	Цветовая темпера- тура	Световой поток	Угол рассеи- вания
V1-I0-70078-04L10-6515050	135W	5000K	18225lm	12°
V1-I0-70078-04L02-6515050	135W	5000K	18225lm	30°
V1-I0-70078-04L07-6515050	135W	5000K	18225lm	60°
V1-I0-70078-04L06-6515050	135W	5000K	18225lm	90°
V1-I0-70078-04L08-6515050	135W	5000K	18225lm	30°x110°
V1-I0-70078-04L10-6515040	135W	4000K	18225lm	12°
V1-I0-70078-04L02-6515040	135W	4000K	18225lm	30°
V1-I0-70078-04L07-6515040	135W	4000K	18225lm	60°
V1-I0-70078-04L06-6515040	135W	4000K	18225lm	90°
V1-I0-70078-04L08-6515040	135W	4000K	18225lm	30°x110°
V1-I0-70078-04L10-65150430	135W	3000K	17550lm	12°
V1-I0-70078-04L02-6515030	135W	3000K	17550lm	30°
V1-I0-70078-04L07-6515030	135W	3000K	17550lm	60°
V1-I0-70078-04L06-6515030	135W	3000K	17550lm	90°
V1-I0-70078-04L08-6515030	135W	3000K	17550lm	30°x110°





Olymp



Угол поворота – 180°
Размер светильника:
426×431×347mm
Размер упаковки
светильника:
476×481×252mm
PF ≥ 0,97

○ металл

Артикул	Мощ- ность	Цветовая темпера- тура	Световой поток	Угол рассеи- вания
V1-I0-70096-04L10-6518050	160W	5000K	21600lm	12°
V1-I0-70096-04L02-6518050	160W	5000K	21600lm	30°
V1-I0-70096-04L07-6518050	160W	5000K	21600lm	60°
V1-I0-70096-04L06-6518050	160W	5000K	21600lm	90°
V1-I0-70096-04L08-6518050	160W	5000K	21600lm	30°x110°
V1-I0-70096-04L10-6518040	160W	4000K	21600lm	12°
V1-I0-70096-04L02-6518040	160W	4000K	21600lm	30°
V1-I0-70096-04L07-6518040	160W	4000K	21600lm	60°
V1-I0-70096-04L06-6518040	160W	4000K	21600lm	90°
V1-I0-70096-04L08-6518040	160W	4000K	21600lm	30°x110°
V1-I0-70096-04L10-6518030	160W	3000K	20800lm	12°
V1-I0-70096-04L02-6518030	160W	3000K	20800lm	30°
V1-I0-70096-04L07-6518030	160W	3000K	20800lm	60°
V1-I0-70096-04L06-6518030	160W	3000K	20800lm	90°
V1-I0-70096-04L08-6518030	160W	3000K	20800lm	30°x110°



Угол поворота – 180°
Размер светильника:
426×431×347mm
Размер упаковки
светильника:
476×481×252mm
PF ≥ 0,97

○ металл

Артикул	Мощ- ность	Цветовая темпера- тура	Световой поток	Угол рассеи- вания
V1-I0-70096-04L10-6524050	215W	5000K	29025lm	12°
V1-I0-70096-04L02-6524050	215W	5000K	29025lm	30°
V1-I0-70096-04L07-6524050	215W	5000K	29025lm	60°
V1-I0-70096-04L06-6524050	215W	5000K	29025lm	90°
V1-I0-70096-04L08-6524050	215W	5000K	29025lm	30°x110°
V1-I0-70096-04L10-6524040	215W	4000K	29025lm	12°
V1-I0-70096-04L02-6524040	215W	4000K	29025lm	30°
V1-I0-70096-04L07-6524040	215W	4000K	29025lm	60°
V1-I0-70096-04L06-6524040	215W	4000K	29025lm	90°
V1-I0-70096-04L08-6524040	215W	4000K	29025lm	30°x110°
V1-I0-70096-04L10-6524030	215W	3000K	27950lm	12°
V1-I0-70096-04L02-6524030	215W	3000K	27950lm	30°
V1-I0-70096-04L07-6524030	215W	3000K	27950lm	60°
V1-I0-70096-04L06-6524030	215W	3000K	27950lm	90°
V1-I0-70096-04L08-6524030	215W	3000K	27950lm	30°x110°

