




|                  |                    |
|------------------|--------------------|
| <b>Type:</b>     | MMS-P pan head     |
| <b>Material:</b> | steel, hardened    |
| <b>Surface:</b>  | bright zinc plated |
| <b>Recess:</b>   | T-Drive            |

Color code  
HECO-Label



| Size<br>D x L [mm] | Article No. | Drill<br>diameter<br>d <sub>0</sub> [mm] | Clamping<br>strength<br>t <sub>fix</sub> [mm] | Head<br>diameter<br>[mm] | Recess | Ap-<br>proval | Packing<br>unit<br>[pcs.] | Pieces per<br>outer carton<br>[pcs.] | Pieces per<br>pallet<br>[pcs.] | Gross price<br>[€/100 pcs.] |
|--------------------|-------------|------------------------------------------|-----------------------------------------------|--------------------------|--------|---------------|---------------------------|--------------------------------------|--------------------------------|-----------------------------|
|--------------------|-------------|------------------------------------------|-----------------------------------------------|--------------------------|--------|---------------|---------------------------|--------------------------------------|--------------------------------|-----------------------------|

## VARIANTA - BOXES FOR PROFESSIONALS

|      |    |                    |     |    |      |      |   |     |       |        |       |
|------|----|--------------------|-----|----|------|------|---|-----|-------|--------|-------|
| 5,0  | 30 | 21685 <sup>*</sup> | 4,0 | 1  | 7,9  | T-20 |   | 200 | 2.000 | 96.000 | 14,70 |
|      | 50 | 21733 <sup>*</sup> | 4,0 | 15 | 7,9  | T-20 |   | 200 | 2.000 | 96.000 | 16,10 |
| 6,0  | 30 | 22098 <sup>*</sup> | 5,0 | 1  | 11,6 | T-30 |   | 200 | 2.000 | 96.000 | 15,20 |
|      | 40 | 20410 <sup>*</sup> | 5,0 | 5  | 11,6 | T-30 |   | 200 | 2.000 | 96.000 | 16,25 |
|      | 50 | 37316              | 5,0 | 5  | 11,6 | T-30 | O | 100 | 1.000 | 48.000 | 17,00 |
|      | 60 | 37129              | 5,0 | 15 | 11,6 | T-30 | O | 100 | 1.000 | 48.000 | 29,65 |
|      | 80 | 37130              | 5,0 | 35 | 11,6 | T-30 | O | 50  | 500   | 24.000 | 47,70 |
| 7,5  | 25 | 22341 <sup>*</sup> | 6,0 | 1  | 13,6 | T-40 |   | 200 | 2.000 | 96.000 | 17,20 |
|      | 45 | 37131              | 6,0 | 1  | 13,6 | T-40 | O | 100 | 1.000 | 48.000 | 26,55 |
|      | 50 | 37132              | 6,0 | 5  | 13,6 | T-40 | O | 100 | 1.000 | 48.000 | 30,25 |
|      | 70 | 42602              | 6,0 | 15 | 13,6 | T-40 | • | 100 | 1.000 | 48.000 | 54,80 |
| 10,0 | 70 | 41143              | 8,0 | 5  | 17,0 | T-40 | • | 50  | 500   | 24.000 | 69,70 |

- = according to ETA 05/0010

O = according to the German DIBt-approval no. Z-21.1-1503

\*Not qualified for fastenings in case of fire