


DIN 914
ISO 4027
Pidätinruuvi, teräväpäinen
Hexagon socket set screw, cone point
Винт установочный с острым концом с внутренним шестигранником
Seadekruvi, terava otsaga


d	M3	M4	M5	M6	M8	M10	M12	M16
s	1,5	2	2,5	3	4	5	6	8

d	L(mm)	A4 3016	St 45 H 0256
M3	4	▲	
	5	■	■
	6	▲	▲
	8	▲	▲
	10		■
	12		■
M4	5	▲	▲
	6	▲	▲
	8	▲	▲
	10	▲	▲
	12	▲	▲
	16	▲	▲
M5	5	▲	■
	6	▲	▲
	8	▲	▲
	10	▲	▲
	12	▲	▲
	16	▲	▲
	20	▲	▲
	25		▲

d	L(mm)	A4 3016	St 45 H 0256
M6	6	▲	▲
	8	▲	▲
	10	▲	▲
	12	▲	▲
	16	▲	▲
	20	▲	▲
	25	▲	▲
	30	■	▲
M8	8	▲	▲
	10	▲	▲
	12	▲	▲
	16	▲	▲
	20	▲	▲
	25	▲	■
	30	▲	▲
	35		▲
M10	40		■
	10	▲	▲
	12	▲	▲
	16	▲	▲
	20	▲	▲
	25	■	▲
	30	■	■
	40	■	▲
	50		▲

d	L(mm)	A4 3016	St 45 H 0256
M10	10	▲	▲
	12	▲	▲
	16	▲	▲
	20	▲	▲
	25	■	▲
	30	■	■
	40	■	▲
	50		▲
M12	12	▲	
	16	▲	
	20	▲	▲
	25	▲	▲
	30	▲	▲
	40	■	
	50	■	
M16	16	■	
	20	■	
	25	■	
	30	■	
	35	■	
	40	■	