

Насосы NB, NK

Тип насоса		d5 [мм]	Диаметр уплотнения вала [мм]
32 -	125.1	24	28
	125	24	28
	160.1	24	28
	160	24	28
	200.1	24	28
	200	24	28
40 -	250	24	28
	125	24	28
	160	24	28
	200	24	28
	250	24	28
50 -	315	32	38
	125	24	28
	160	24	28
	200	24	28
	250	24	28
65 -	315	32	38
	125	24	28
	160	24	28
	200	24	28
	250	32	38
80 -	315	32	38
	160	24	28
	200	32	38
	250	32	38
	315	32	38
100 -	315*	42	48
	400	42	48
	160	24	28
	200	32	38
	250	32	38
125 -	250*	42	48
	315	32	38
	315*	42	48
	400	42	48
	200	32	38
150 -	250	32	38
	250*	42	48
	315	42	48
	315	42	48
	400	42	48
200 -	400 ²⁾	48	55
	450 ²⁾	48	55
	350	48	55
	400	48	55
	450 ²⁾	60	60
250 -	500	60	60

* Увеличенный насос.

1) Не доступно в исполнении NB.

2) Не доступно в исполнении из нержавеющей стали.

Насосы NBG, NKG

Тип насоса		d5 [мм]	Диаметр уплотнения вала [мм]
50 -	32 -	125.1	24
		125	24
		160.1	24
		160	24
		200.1	24
		200	24
65 -	50 -	250	32
		125	24
		160	24
		200	24
		250	32
80 -	40 -	315	32
		125	24
		160	24
		200	24
		250	32
100 -	65 -	315	32
		125	24
		160	24
		200	24
		250	32
125 -	80 -	315	32
		125	24
		160	32
		200	32
		250	32
150 -	100 -	315	42
		160	32
		200	32
		250	42
		400	42
200 -	125 -	400.1	42
		400	42
		400	48
		400,1	42
		160	32
250 -	150 -	200	32
		250	42
		315	42
		400	42
		200	32
300 -	200 -	250	42
		315,2	42
		315,2	48
		315	48
		400	48
350 -	250 -	500	60
		400 ²⁾	48
		450 ²⁾	48
		350	48
		400	48
350 -	300 -	450 ²⁾	60
		500	60
350 -	300 -	305 ²⁾	48
		55	55

2) Не доступно в исполнении из нержавеющей стали.