

Облегчённые трубчатые насечные кабельные наконечники „Т“


light

- Из трубки
- Материал: 99,9% из электролитной меди E-CU DIN 40500
- Поверхность: луженые
- со смотровым отверстием



Cu

№ арт.	псп	M	d2	d1	d4	A	Од	Kr/100		YE
294150	240	12	13,2	21,2	26,4	37,0	90,0	13,300	30	10
294152		14	14,5	21,2	26,4	37,0	90,0	13,000	30	10
294154 *		16	16,5	21,2	26,4	37,0	90,0	15,000	30	10
294160	300	12	13,2	23,4	28,6	40,0	96,0	15,400	16	8
294162		14	14,5	23,4	28,6	40,0	96,0	15,000	16	8
294164		16	16,5	23,4	28,6	40,0	96,0	2,900	16	8
294174	400	16	16,5	26,8	32,8	37,0	104,7	22,700	10	5
294176		20	21,0	26,8	32,8	37,0	104,7	22,000	10	5
294184	500	16	16,5	29,8	38,4	46,5	115,5	42,000	8	3
294196	630	20	21,0	34,5	44,7	50,0	133,0	66,800	6	3



Облегчённые стыковые соединители „М“

light

- Материал: 99,9% из электролитной меди E-CU DIN 40500
- Поверхность: луженые



Cu

№ арт.	псп	d1	d4	Од	Kr/100		YE
294200	1,5	2,4	4,0	22,0	0,080	2000	200
294202	2,5	2,7	4,3	22,0	0,080	2000	200
294204	4	3,1	4,8	25,0	0,300	1000	100
294206	6	3,8	5,5	25,0	0,300	1000	100
294208	10	4,7	6,9	25,0	0,400	600	100
294210	16	5,6	7,8	29,0	0,500	500	100
294212	25	7,1	9,5	29,0	0,700	200	50
294214	35	8,2	11,0	35,0	1,200	200	50
294218	50	9,5	12,5	35,0	1,400	100	40
294220	70	11,5	15,0	45,0	2,700	50	20
294222	95	13,5	17,0	47,0	3,200	50	20
294224	120	15,6	20,0	52,0	5,500	50	20
294226	150	16,5	21,0	59,0	6,500	50	20
294228	185	18,4	23,6	65,0	9,200	36	20
294230	240	21,2	26,4	75,0	11,900	12	10
294232	300	23,4	28,6	90,0	14,500	6	5
294234	400	26,8	32,8	106,0	24,200	6	5

