

Прессованные кабельные наконечники DIN


DIN

- материал: 99,9% электролитная медь, отожжённый материал
- размер трубки по стандарту DIN 46235
- поверхность: лужёная, исполнение с 2-мя прорезями
- выдавленная маркировка



Cu

№ арт.	псп	M	УН	d2	d1	d4	A	Д	c1	c2	Kr/100	УЕ
290550	70	12	16	13,0	11,5	16,5	28,0	55,0	13,0	13,0	10,800	25
290552	95	12	18	13,0	13,5	19,0	35,0	65,0	13,0	13,0	14,800	20
290554	120	12	20	13,0	15,5	21,0	35,0	70,0	16,0	17,0	18,600	25
290556	150	12	22	13,0	17,0	23,5	35,0	78,0	16,0	17,0	26,200	25
290558	185	12	25	13,0	19,0	25,5	40,0	82,0	16,0	17,0	26,800	10
290560	240	12	28	13,0	21,5	29,0	40,0	92,0	16,0	17,0	40,200	10



Изогнутые кабельные наконечники, 90° DIN 46235


DIN

- материал: 99,9% электролитная медь, отожжённый материал
- размер трубки по стандарту DIN 46235
- поверхность: лужёная
- выдавленная маркировка



Cu

№ apr.	псп	M	УН	d2	d1	d4	A	v1	v2	c1	c2	Kr/100	YE
291700	6	5	5	5,3	3,8	5,5	10,0	2	-	6,5	9,0	0,400	100
291702	*	6	5	6,4	3,8	5,5	10,0	2	-	7,5	10,0	0,300	100
291704	10	5	6	5,3	4,5	6,0	10,0	2	-	7,0	10,0	0,400	100
291706		6	6	6,4	4,5	6,0	10,0	2	-	7,5	10,0	0,500	100
291708		8	6	8,4	4,5	6,0	10,0	2	-	10,0	13,0	1,100	100
291710	16	6	8	6,4	5,5	8,5	20,0	2	1	7,5	11,0	1,200	50
291712	*	8	8	8,4	5,5	8,5	20,0	2	1	10,0	13,0	1,100	50
291714		10	8	10,5	5,5	8,5	20,0	2	1	12,0	15,0	1,200	50
291716		12	8	13,0	5,5	8,5	20,0	2	1	13,0	18,0	1,200	50
291718	25	6	10	6,4	7,0	10,0	20,0	2	1	7,5	11,0	1,500	50
291720	*	8	10	8,4	7,0	10,0	20,0	2	1	10,0	13,0	1,500	50
291722		10	10	10,5	7,0	10,0	20,0	2	1	12,0	15,0	1,500	50
291724		12	10	13,0	7,0	10,0	20,0	2	1	13,0	18,0	1,500	50
291726	*	8	12	8,4	8,2	12,5	20,0	2	1	10,0	13,0	2,600	25
291728		10	12	10,5	8,2	12,5	20,0	2	1	12,0	15,0	2,900	25
291730		12	12	13,0	8,2	12,5	20,0	2	1	13,0	18,0	2,900	25
291732	50	8	14	8,4	10,0	14,0	28,0	3	1	10,0	16,0	4,100	25
291734	*	10	14	10,5	10,0	14,0	28,0	3	1	12,0	16,0	4,200	20
291736		12	14	13,0	10,0	14,5	28,0	3	1	13,0	18,0	4,500	20
291738		16	14	17,0	10,0	14,5	28,0	3	1	16,0	22,0	4,100	20
291740	70	8	16	8,4	11,5	16,5	28,0	3	1	10,0	14,0	5,400	30
291742	*	10	16	10,5	11,5	16,5	28,0	3	1	12,0	16,0	5,500	30
291744		12	16	13,0	11,5	16,5	28,0	3	1	13,0	18,0	6,000	15
291746		16	16	17,0	11,5	16,5	28,0	3	1	16,0	22,0	5,600	30
291748	95	10	18	10,5	13,5	19,0	35,0	4	2	12,0	17,0	8,400	10
291750		12	18	13,0	13,5	19,0	35,0	4	2	13,0	18,0	8,700	10
291752		16	18	17,0	13,5	19,0	35,0	4	2	16,0	22,0	8,700	10
291754	120	10	20	10,5	15,5	21,0	35,0	4	2	15,0	17,0	10,000	20
291756	*	12	20	13,0	15,5	21,0	35,0	4	2	16,0	18,0	10,000	20
291758		16	20	17,0	15,5	21,0	35,0	4	2	18,0	22,0	10,200	20
291760		20	20	21,0	15,5	21,0	35,0	4	2	21,0	24,0	9,800	15
291762	150	10	22	10,5	17,0	23,5	35,0	4	2	15,0	17,0	13,100	15
291764	*	12	22	13,0	17,0	23,5	35,0	4	2	16,0	18,0	13,200	15
291766		16	22	17,0	17,0	23,5	35,0	4	2	19,0	22,0	14,100	15
291768		20	22	21,0	17,0	23,5	35,0	4	2	21,0	24,0	13,700	10
291770	185	10	25	10,5	19,0	25,5	40,0	4	2	15,0	22,0	16,400	10
291772		12	25	13,0	19,0	25,5	40,0	4	2	16,0	22,0	15,600	10
291774		16	25	17,0	19,0	25,5	40,0	4	2	19,0	22,0	18,600	10
291776		20	25	21,0	19,0	25,5	40,0	4	2	21,0	24,0	17,500	10
291778	240	12	28	13,0	21,5	29,0	40,0	5	2	16,0	22,0	22,400	10
291780		16	28	17,0	21,5	29,0	40,0	5	2	19,0	22,0	22,900	10
291782		20	28	21,0	21,5	29,0	40,0	5	2	21,0	24,0	21,000	10



haupa®

...решения которые убеждают

HAUPA GmbH & Co. KG, Königstr. 165-169, 42853 Remscheid, телефон: +49 (0)2191 8418-0, факс: +49 (0)2191 8418-840, sales@haupa.com