



Diffuse mode sensor RLK39-8-800-Z/31/40a/116




- Infrared light
- Light-on/dark-on, switchable
- Timer function
- Degree of protection IP67

Diffuse mode sensor



Dimensions



Release date: 2020-12-10 Date of issue: 2020-12-10 Filename: 088834_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

General specifications

Detection range	0 ... 800 mm
Adjustment range	150 ... 800 mm
Reference target	standard white 200 mm x 200 mm
Light source	IREd
Light type	modulated infrared light
Ambient light limit	IEC / EN 60947-5-2 , 10000 Lux

Functional safety related parameters

MTTF _d	803 a
Mission Time (T _M)	20 a
Diagnostic Coverage (DC)	0 %

Indicators/operating means

Function indicator	LED yellow: switching state LED red: pre-fault indication
Control elements	Sensing range adjuster, light-on/dark-on changeover switch
Control elements	switch for timer function

Electrical specifications

Operating voltage	U _B	12 ... 240 V DC 24 ... 240 V AC (50 ... 60 Hz)
Ripple		10 %
No-load supply current	I ₀	≤ 50 mA
Protection class		II, rated voltage ≤ 250 V AC with pollution degree 1-2 according to IEC 60664-1 Caution! The protection class 2 is only valid when the terminal compartment is closed. output circuit has basic insulation to control circuit according to IEC/EN 61140
Power consumption	P ₀	≤ 3 VA
Time delay before availability	t _v	≤ 300 ms

Output

Switching type	light/dark on	
Signal output		1 relay output
Switching voltage	max. 240 V AC ; 150 V DC	
Switching current		max. 3 A
Switching power	DC: max. 90 W AC: max. 750 VA	
Switching frequency	f	≤ 25 Hz
Response time	≤ 20 ms	
Timer function		On-/off-delay or pulse extension on choice

Conformity

Product standard	EN 60947-5-2
------------------	--------------

Approvals and certificates

EAC conformity	TR CU 020/2011 TR CU 004/2011
CCC approval	Certified by China Compulsory Certification (CCC)
Approvals	CE

Ambient conditions

Ambient temperature	-25 ... 55 °C (-13 ... 131 °F)
Storage temperature	-40 ... 70 °C (-40 ... 158 °F)

Mechanical specifications



Housing width	25 mm
Housing height	64 mm
Housing depth	75 mm
Degree of protection	IP67
Connection	terminal compartment PG9, ≤ 2.5 mm ²
Material	
Housing	PBT
Optical face	PMMA

Release date: 2020-12-10 Date of issue: 2020-12-10 Filename: 088834_eng.pdf


Technical Data

Mass	approx. 110 g
General information	
Scope of delivery	Mounting aid

Connection Assignment



Characteristic Curve




Release date: 2020-12-10 Date of issue: 2020-12-10 Filename: 088834_eng.pdf

Mounting

Timerfunktion
Fonction de temporisation
Funzione timer


Timer function
Función del timer



Accessories

	OMH-RL39	Mounting bracket for RL39 series Sensors
---	----------	--

Configuration



○ Denotes Light - ON T= 0.1 10 sec.

● Denotes Dark - ON