





Data Matrix tag

PGV85-CT4

- High chemical resistance
- Low weight
- Self-adhesive mounting
- High temperature resistance

Data Matrix tag for PGV system

Dimensions



Technical Data

General specifications

Number interval	1 ... 99999999 = TAG number (see Order Information)
Length	87 mm
Width	87 mm

Ambient conditions

Operating temperature	-40 ... 100 °C (-40 ... 212 °F)
Installation temperature	10 ... 40 °C (50 ... 104 °F)
Environmental resistance	UV radiation Humidity Salt spray (150 h / 5%)
Chemical resistance	Oils Grease Fuels Aliphatic solvents Weak acids

Mechanical specifications

Material thickness	100 µm
Material	polyester
Surface	polyester , glossy
Tensile strength	≥ 50 N

Release date: 2021-12-22 Date of issue: 2022-01-04 Filename: 282530_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data


Adhesive	Acrylate-based adhesive ; curing 72 h
Adhesive strength	Average values (FTM2) Aluminum : 24 N / 25 mm High grade stainless steel : 25 N / 25 mm ABS : 22 N / 25 mm PP : 18 N / 25 mm HD-PE : 12 N / 25 mm LD-PE : 12 N / 25 mm
Note	To improve readability and protect the Data Matrix tag from mechanical damage, the protective film PGV25M-CD160-CLEAR must be adhered over the Data Matrix tag.
General information	
Ordering information	The required tag numbers are entered in the additional text for the job in the form of the start and end position. The order quantity must match the specified range.

Accessories

	PGV25M-CD160-CLEAR	Protective laminate for PGV code tape
	PGV25M-CD100-CLEAR	Protective laminate for PGV code tape

Type Code

Order Information



Release date: 2021-12-22 Date of issue: 2022-01-04 Filename: 282530_eng.pdf