




Stack light siren element VAZ-HORN-40MM-85DBA-2TONE

- Modular design
- Bayonet system for simple mounting and dismounting
- 2 different tone options
- 40-mm-series

Stack light siren element, 2 tones



Dimensions



Technical Data

General specifications		
Signal type		Continuous tone, pulse tone
UL File Number		E223176
Color		grey
Frequency		2.9 kHz
Loudness		85 dB
Electrical specifications		
Rated operating voltage	U _e	24 V AC/DC
Rated operating current	I _e	≤ 80 mA
Inrush current		500 mA
Ambient conditions		
Ambient temperature		-30 ... 60 °C (-22 ... 140 °F)
Mechanical specifications		
Degree of protection		IP66
Connection		Bayonet system
Material		PC

Release date: 2020-06-29 Date of issue: 2020-06-29 Filename: 324828_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Technical Data

Mass	25 g
Life span	min. 5000 hours

Matching system components

	VAZ-CLAMP-40MM-IO	Signal tower connection element IO-Link with cover
	VAZ-CLAMP-40MM	Stack light terminal base with cover plate

Release date: 2020-06-29 Date of issue: 2020-06-29 Filename: 324828_eng.pdf