





Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited.
未经允许禁止传输、复制、编辑该文档，以及利用其内容进行交流

借通用件登记
Common Part

原图号
Old Draw. No.

底图总号
Assembly No.

REVISION RECORD				
REV	CN	DESCRIPTION	DRFT	DATE



HOW TO ORDER:
4508 XX - XX - KXXX
Series No. Poles: 02:02 contacts
03:03 contacts
...
24:24 contacts
Color: N/A:Light grey
Customer request

NOTES:

UL/CUL Standard

1.Rated Voltage/Current :

Use group	B	C	D
Rated voltage(V)	300	—	300
Rated current(A)	15	—	10

IEC Standard

1.Rated Voltage/Current :

Surge voltage category	III	III	II
Pollution degree	3	2	2
Rated surge voltage(KV)	4.0	4.0	4.0
Rated voltage(V)	320	320	630
Rated current(A)	16	16	16

Material:

Insulator	PA66	UL94 V-0
Conductor	COPPER ALLOY	Sn,Plated

General information:

- 1.Dimension shall be interpreted per ASME Y14.5-2009
- 2.Pitch : 5.00mm, Poles : 02~24P
- 3.Operating temperature: -40°C~+105°C
Wave soldering temperature: 260°C±5°C; time: 5s
- 4.RoHS Compliance
- 5.Undimensioned Tolerances:

Pitch Range In mm		Nominal Dimension Range In mm							—	∩	□
TO 6	Over 6 TO 10	Over 10 TO 24	TO 30	Over 30 TO 60	Over 60 TO 100	Over 100 TO 150	Over 150		0.1/10		
	±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2'		

订货号 Order No.	4508XX		名 称 Name	450针座连接器 -弯型防错	未注公差 Tolerance	表面 Surface		
项 目 Item	签 字 Signature	日 期 Date			Tolerance Table	VDI21		
设 计 Design	JCY	2024.06.25	图 号 Drawing No.	PRM000437	版本号 Revision Number	重量 Weight	比例 Scale	
审 核 Check	BYH	2024.06.25	材 料 Material	Notes	M2		1:1	
工 艺 Process	-	-	物料号 Item No.	411095524	第1页/共1页 1 of 1		mm	
标 准 化 Unify	-	-		...	SUPU 宁波速普电子有限公司			
批 准 Approve	XJ	2024.06.25		411095546	NINGBO SUPU ELECTRONICS CO.,LTD.			