


Для компактных люминесцентных ламп
Модель: 28x41 мм

Класс защиты I



Платформа				ГПА										Конденсатор	
Мощность	Тип	Цоколь	Ток	Тип	Номер для заказа	В, Гц	a	b	c	Вес	$\Delta t / \Delta t_{н}$	EEL	C_p	Ток	
Вт			мА				мм	мм	мм	кг	К		мФ	мА	
220 В, 50Гц															
18	ТСД/ТСТ	G24d2/GX24d2	220	IN 18L880	509261	220, 50	85	75	27	0,28	50/125	—	2,0	110	
18	ТСF/ТСЛ	2G10/2G11	370	118.933	534624	220, 50	150	140	45	0,43	70/160	—	4,5	120	
18	ТУ	2G13	370	118.933	534624	220, 50	150	140	45	0,43	70/160	—	4,5	120	
2x18	ТСF/ТСЛ	2G10/2G11	400	136.158	530252**	220, 50	150	140	45	0,43	65	—	4,0	210	
24	ТСF/ТСЛ	2G10/2G11	345	118.933	534624	220, 50	150	140	45	0,43	70/160	—	4,5	150	
26	ТСД/ТСТ	G24d3/GX24d3	325	118.933	534624	220, 50	150	140	45	0,43	70/160	—	3,5	140	
28	ТСDD	GR8/GR10q	320	118.933	534624	220, 50	150	140	45	0,43	70/160	—	3,5	150	
36	ТСF/ТСЛ	2G10/2G11	430	136.158	530252**	220, 50	150	140	45	0,43	65	—	4,0	210	
36/40	ТУ/ТР	2G13/G10q	430	136.158	530252**	220, 50	150	140	45	0,43	65	—	4,0	210	
38	ТСDD	GR10q	430	136.158	530252**	220, 50	150	140	45	0,43	65	—	4,0	210	
58	ТУ	2G13	670	158.625	164828	220, 50	190	180	92	0,80	55/155	—	7,0	320	
220 В, 50Гц – 26x41 мм															
18	ТСF/ТСЛ	2G10/2G11	370	118.257	534146	220, 50	155	137	60	0,51	70/115	—	4,0	120	
2x18	ТСF/ТСЛ	2G10/2G11	370	136.170	527460**	220, 50	155	137	60	0,50	70/175	—	4,0	210	
24	ТСF/ТСЛ	2G10/2G11	345	118.257	534146	220, 50	155	137	60	0,51	70/115	—	4,0	150	
26	ТСД/ТСТ	G24d3/GX24d3	325	118.257	534146	220, 50	155	137	60	0,51	70/115	—	4,0	140	
36	ТСF/ТСЛ	2G10/2G11	430	136.170	527460**	220, 50	155	137	60	0,50	70/175	—	4,0	210	
230 В, 50 Гц															
18	ТСД/ТСТ	G24d2/GX24d2	220	IN 18L940	508922	230, 50	85	75	34	0,32	50/120	81	2,0	110	
IN 18L319				163763	230, 50	85	75	34	0,32	60/140	81	2,0	110		
IN 18L850				503871	230, 50	85	75	27	0,28	65/165	82	2,0	110		
18	ТСF/ТСЛ	2G10/2G11	370	IN 18.510	164572	230, 50	155	140	92	0,80	40/65	81	4,5	120	
IN 18.131				530941	230, 50	150	140	60	0,55	55/95	82	4,5	120		
118.934**				534621	230, 50	150	140	45	0,43	70/150	—	4,5	120		
18	ТУ	2G13	370	IN 18.131	530941	230, 50	150	140	60	0,55	55/95	82	4,5	120	
118.934**				534621	230, 50	150	140	45	0,43	70/150	—	4,5	190		
2x18	ТСF/ТСЛ	2G10/2G11	400	IN 2x18.135	532155	230, 50	150	140	45	0,43	65	81	4,0	210	
				136.334	530007	230, 50	150	140	60	0,55	60/155	81	4,0	210	
21	ТСDD	GR10q	260	IN 21.803	169651	230, 50	155	140	53	0,50	45/95	81	3,0	120	
22	ТР	G10q	400	IN 30.330	169503	230, 50	150	140	67	0,60	55/125	82	4,5	200	
24	ТСF/ТСЛ	2G10/2G11	345	IN 24/26.829	179659	230, 50	105	95	53	0,50	60/120	82	4,5	150	
				IN 24/26.804	534490	230, 50	150	140	60	0,55	55/110	82	4,5	150	
				118.934**	534621	230, 50	150	140	45	0,43	70/150	—	4,5	150	
26	ТСД/ТСТ	G24d3/GX24d3	325	IN 18.131	530941	230, 50	150	140	60	0,55	55/95	81	3,5	140	
				IN 26.813	509502	230, 50	110	100	45	0,45	55/145	82	3,5	140	
28	ТСDD	GR8/GR10q	320	IN 18.131	530941	230, 50	150	140	60	0,55	55/95	81	3,5	150	
				IN 18.510	164572	230, 50	155	140	92	0,80	40/65	81	3,5	150	
				118.934**	534621	230, 50	150	140	45	0,43	70/150	—	3,5	150	
32	ТР	G10q	450	IN 36.824	172436	230, 50	150	140	72	0,64	55/125	82	4,0	220	

*** только EN 61347