

■ Медные трубчатые кабельные наконечники, 6–400 мм²

Облегченного типа (стандарт Klauke)

Ном. сечение мм²	Размер отв. под болт Ø	Артикул	Размеры, мм								Масса/ 100 шт. ~ кг	Кол-во в упак. шт.
			d1	a	b	d2	d4	c1	c2	l		
70	M6	7R6	12,0	21	23	6,5	16,5	10,00	10,0	43	4,49	25
	M8	7R8	12,0	21	23	8,5	16,5	10,00	10,0	43	4,38	50
	M10	7R10	12,0	21	23	10,5	16,5	12,00	12,0	44	4,54	50
	M12	7R12	12,0	21	23	13,0	16,5	13,00	13,0	46	4,63	50
	M14	7R14	12,0	21	23	15,0	16,5	14,50	14,5	48	4,76	25
	M16	7R16	12,0	21	28	17,0	16,5	16,00	16,0	50	4,24	25
	M20	7R20	12,0	21	30	21,0	16,5	19,00	19,0	53	5,09	25
95	M8	8R8	13,5	25	26	8,5	18,0	12,0	12,0	48	5,44	25
	M10	8R10	13,5	25	26	10,5	18,0	12,0	12,0	48	5,40	50
	M12	8R12	13,5	25	26	13,0	18,0	13,0	13,0	49	5,56	50
	M14	8R14	13,5	25	26	15,0	18,0	14,5	14,5	51	5,62	25
	M16	8R16	13,5	25	28	17,0	18,0	16,0	16,0	54	5,82	50
	M20	8R20	13,5	25	36	21,0	18,0	22,0	22,0	60	6,71	25
120	M8	9R8	15,0	26	28	8,5	19,5	14,0	14,0	51	6,72	25
	M10	9R10	15,0	26	28	10,5	19,5	14,0	14,0	51	6,57	50
	M12	9R12	15,0	26	28	13,0	19,5	14,0	14,0	51	6,38	50
	M14	9R14	15,0	26	28	15,0	19,5	15,0	15,0	52	6,45	25
	M16	9R16	15,0	26	30	17,0	19,5	16,0	16,0	54	6,51	50
	M20	9R20	15,0	26	36	21,0	19,5	22,0	22,0	63	7,74	25
150	M8	10R8	16,5	30	31	8,5	21,0	14,0	14,0	56	7,78	10
	M10	10R10	16,5	30	31	10,5	21,0	14,0	14,0	56	7,62	10
	M12	10R12	16,5	30	31	13,0	21,0	15,0	15,0	57	7,73	25
	M14	10R14	16,5	30	31	15,0	21,0	15,0	15,0	57	7,64	10
	M16	10R16	16,5	30	31	17,0	21,0	16,0	16,0	58	7,53	10
	M20	10R20	16,5	30	36	21,0	21,0	22,0	22,0	66	8,80	10
185	M10	11R10	19,0	30	35	10,5	24,0	18,0	18,0	65	11,75	10
	M12	11R12	19,0	30	35	13,0	24,0	18,0	18,0	65	11,82	10
	M14	11R14	19,0	30	35	15,0	24,0	18,0	18,0	65	11,39	10
	M16	11R16	19,0	30	35	17,0	24,0	18,0	18,0	65	11,24	25
	M20	11R20	19,0	30	39	21,0	24,0	22,0	22,0	69	12,00	10
240	M10	12R10	21,0	35	39	10,5	26,0	21,5	19,0	72	14,72	10
	M12	12R12	21,0	35	39	13,0	26,0	21,5	19,0	72	14,55	10
	M14	12R14	21,0	35	39	15,0	26,0	21,5	19,0	72	14,24	10
	M16	12R16	21,0	35	39	17,0	26,0	21,5	19,0	72	14,09	25
	M20	12R20	21,0	35	39	21,0	26,0	21,5	19,0	72	13,60	10
300	M12	13R12	23,5	44	43	13,0	29,5	24,0	24,0	87	23,33	5
	M14	13R14	23,5	44	43	15,0	29,5	24,0	24,0	87	23,14	5
	M16	13R16	23,5	44	43	17,0	29,5	24,0	24,0	87	22,74	5
	M20	13R20	23,5	44	43	21,0	29,5	24,0	24,0	87	22,19	5
400	M12	14R12	27,0	44	49	13,0	34,0	24,0	24,0	90	32,41	5
	M14	14R14	27,0	44	49	15,0	34,0	24,0	24,0	90	32,24	5
	M16	14R16	27,0	44	49	17,0	34,0	24,0	24,0	90	31,98	5
	M20	14R20	27,0	44	49	21,0	34,0	24,0	24,0	90	31,41	5

■ Медные втулки для уплотненных многопроволочных жил, а также втулки для 3- и 4-секторных жил указаны в главе «Медные втулки для уплотненных многопроволочных и секторных жил», стр. 100.

► Выбор инструмента: см. таблицу на стр. 55.