

■ **Медные угловые трубчатые кабельные наконечники, 6–400 мм², угол 45°**
Облегченного типа (стандарт Klauke)

Ном. сечение мм²	Размер отв. под болт Ø	Артикул	Размеры, мм							Масса/100 шт. ~ кг	Кол-во в упак. шт.
			d1	a	b	d2	d4	c1	l3		
70	M6	47R645	12,0	21	23	6,5	16,5	10,0	13	5,06	25
	M8	47R845	12,0	21	23	8,5	16,5	10,0	14	5,06	25
	M10	47R1045	12,0	21	23	10,5	16,5	12,0	16	5,25	25
	M12	47R1245	12,0	21	23	13,0	16,5	13,0	18	5,30	25
	M14	47R1445	12,0	21	23	15,0	16,5	14,5	20	5,60	25
	M16	47R1645	12,0	21	28	17,0	16,5	16,0	22	5,61	25
	M20	47R2045	12,0	21	30	21,0	16,5	19,0	24	5,60	25
95	M8	48R845	13,5	25	26	8,5	18,0	12,0	14	6,19	25
	M10	48R1045	13,5	25	26	10,5	18,0	12,0	17	5,70	25
	M12	48R1245	13,5	25	26	13,0	18,0	13,0	18	6,67	25
	M14	48R1445	13,5	25	26	15,0	18,0	14,5	20	6,60	25
	M16	48R1645	13,5	25	28	17,0	18,0	16,0	22	6,78	25
	M20	48R2045	13,5	25	36	21,0	18,0	22,0	24	6,80	25
120	M8	49R845	15,0	26	28	8,5	19,5	14,0	16	7,92	10
	M10	49R1045	15,0	26	28	10,5	19,5	14,0	17	7,99	10
	M12	49R1245	15,0	26	28	13,0	19,5	14,0	18	7,96	10
	M14	49R1445	15,0	26	28	15,0	19,5	15,0	20	7,94	10
	M16	49R1645	15,0	26	30	17,0	19,5	16,0	22	8,26	10
	M20	49R2045	15,0	26	36	21,0	19,5	22,0	24	8,20	10
150	M8	50R845	16,5	30	31	8,5	21,0	14,0	16	9,00	10
	M10	50R1045	16,5	30	31	10,5	21,0	14,0	17	9,15	10
	M12	50R1245	16,5	30	31	13,0	21,0	15,0	18	8,75	10
	M14	50R1445	16,5	30	31	15,0	21,0	15,0	20	9,20	10
	M16	50R1645	16,5	30	31	17,0	21,0	16,0	22	9,22	10
	M20	50R2045	16,5	30	36	21,0	21,0	22,0	24	9,26	10
185	M10	51R1045	19,0	30	35	10,5	24,0	18,0	22	13,30	10
	M12	51R1245	19,0	30	35	13,0	24,0	18,0	22	13,32	10
	M14	51R1445	19,0	30	35	15,0	24,0	18,0	22	13,40	10
	M16	51R1645	19,0	30	35	17,0	24,0	18,0	22	12,80	10
	M20	51R2045	19,0	30	39	21,0	24,0	22,0	24	13,10	10
240	M10	52R1045	21,0	35	39	10,5	26,0	21,5	22	16,28	10
	M12	52R1245	21,0	35	39	13,0	26,0	21,5	22	16,80	10
	M14	52R1445	21,0	35	39	15,0	26,0	21,5	22	16,40	10
	M16	52R1645	21,0	35	39	17,0	26,0	21,5	22	16,10	10
	M20	52R2045	21,0	35	39	21,0	26,0	21,5	24	16,10	10
300	M12	53R1245	23,5	44	43	13,0	29,5	24,0	24	24,08	5
	M14	53R1445	23,5	44	43	15,0	29,5	24,0	24	24,20	5
	M16	53R1645	23,5	44	43	17,0	29,5	24,0	24	23,23	5
	M20	53R2045	23,5	44	43	21,0	29,5	24,0	24	23,50	5
400	M12	54R1245	27,0	44	49	13,0	34,0	24,0	24	34,00	5
	M14	54R1445	27,0	44	49	15,0	34,0	24,0	24	33,40	5
	M16	54R1645	27,0	44	49	17,0	34,0	24,0	24	34,28	5
	M20	54R2045	27,0	44	49	21,0	34,0	24,0	24	31,80	5

■ Медные втулки для уплотненных многопроволочных жил, а также втулки для 3- и 4-секторных жил указаны в главе «Медные втулки для уплотненных многопроволочных и секторных жил», стр. 100.

► Выбор инструмента: см. таблицу на стр. 55.