PRODUCT CARD

25.12.2017

KE61.2T

клеммы

Тип	KE61.2T
GTIN	6418677192333
Название	клеммы Ensto Clampo Pro 3 x KE61.2 синий, Al 6-50 мм², Cu 2.5-50 мм²
Описание	"Ensto Clampo Apparatus" - это универсальная серия клемм общего назначениядля подключения к оборудованию алюминиевых и медных проводников 2,5 – 240 мм².
Вендор	Ensto Finland Oy

Техническая спецификация

Technical specification

Содержание:	KE61.2 x 3

Dimensions

Масса:	0.09 kg
Поперечное сечение проводника:	Cu 2,5-50 Al 6-50

Temperatures

Температура эксплуатации:	≤ 80 °C

Электрические характеристики

Номинальное напряжение изоляции:	800 V
Номинальный ток:	Cu 160 A, Al 145 A
Степень загрязнения:	3

Materials

Корпус:	Полиамид

Colors

Цвет:	Синий

Features

OOO Ensto Rus
Podsosensky per. h.20, build. 1
105 062 Moscow
Russin Federation
email: ensto.russia@ensto.com www.ensto.com
phone: +7 495 661 1039

Головка винта:	Шестигранник
Размер головки винта:	5 mm
Крепеж:	DIN-рейка

Механические характеристики

Момент затяжки:	4 Nm (2.5-4mm²), 12 Nm (6-50mm²)

Certificates

Стандарты:	EN 60947-7-1, EN 61238-1
Класс соединителя:	A
Категория UL:	XCFR2
Номер UL:	E192532, E192532

Ratings

ETIM 7:	EC000897

US specific

Размер проводника:	1/0-6
Максимальное напряжение:	600 V
Момент затяжки:	90 Lb-In
Max. current:	Cu 150A, Al 120A

ETIM

ETIM

Length:	49 mm
Material insulation body:	Thermoplastic
Rated voltage:	800 V
Width/grid dimension:	17.8 mm
Mounting method:	DIN rail (top hat rail) 35 mm
Colour:	Blue
Type of electrical connection 1:	Screw connection
Number of levels:	1
Height at lowest possible mounting height:	43 mm
Operation temperature:	-5 ... 80 °C
Connectable conductor cross section fine-strand with cable end sleeve:	2.5 ... 35 mm²
Number of clamp positions per level:	2
Connectable conductor cross section fine-strand without cable end sleeve:	2.5 ... 35 mm²
Explosion-tested version 'Ex e':	false
Connectable conductor cross section multi-wired:	2.5 ... 50 mm²
Inflammability class of insulation material acc. with UL94:	V2
Rated current In:	145 A
Type of electrical connection 2:	Screw connection
Connection position:	Sideways

Упаковка

В стандартной упаковке

Unit:	PCS
Size:	10

OOO Ensto Rus
Podsosensky per. h.20, build. 1
105 062 Moscow
Russin Federation
email: ensto.russia@ensto.com www.ensto.com
phone: +7 495 661 1039