PRODUCT CARD

25.12.2017

KE62.2T

клеммы



Тип	KE62.2T
GTIN	6418677192371
Название	клеммы Ensto Clampo Pro 3 x KE62.2 синий, Al/Cu 16-95 мм²
Описание	"Ensto Clampo Apparatus" - это универсальная серия клемм общего назначениядля подключения к оборудованию алюминиевых и медных проводников 2,5 – 240 мм².
Вендор	Ensto Finland Oy

Техническая спецификация

Technical specification

Содержание: KE62.2 x 3

Dimensions

Масса: 0.22 kg

Поперечное сечение проводника: 16-95

Temperatures

Температура эксплуатации: ≤ 80 °C

Электрические характеристики

Номинальное напряжение изоляции: 800 V

Номинальный ток: Cu 245 A, Al 220 A

Степень загрязнения: 3

Materials

Корпус: Полиамид

Colors

Цвет: Синий

Features

OOO Ensto Rus
Podsosensky per. h.20, build. 1
105 062 Moscow
Russin Federation
email: ensto.russia@ensto.com www.ensto.com
phone: +7 495 661 1039

Головка винта:	Шестигранник
Размер головки винта:	5 mm
Крепеж:	DIN-рейка

Механические характеристики

Момент затяжки:	20 Nm

Certificates

Стандарты:	EN 60947-7-1, EN 61238-1
Класс соединителя:	A
Категория UL:	XCFR2
Номер UL:	E192532, E192532

Ratings

ETIM 7:	EC000897

US specific

Размер проводника:	4/0-4
Максимальное напряжение:	600 V
Момент затяжки:	126 Lb-In
Max. current:	Cu 230A, Al 180A

ETIM

ETIM

Length:	86 mm
Material insulation body:	Thermoplastic
Rated voltage:	800 V
Width/grid dimension:	24 mm
Mounting method:	DIN rail (top hat rail) 35 mm
Colour:	Blue
Type of electrical connection 1:	Screw connection
Number of levels:	1
Height at lowest possible mounting height:	49 mm
Operation temperature:	-5 ... 80 °C
Connectable conductor cross section fine-strand with cable end sleeve:	16 ... 70 mm²
Number of clamp positions per level:	2
Connectable conductor cross section fine-strand without cable end sleeve:	16 ... 70 mm²
Explosion-tested version 'Ex e':	false
Connectable conductor cross section multi-wired:	16 ... 95 mm²
Inflammability class of insulation material acc. with UL94:	V2
Rated current In:	220 A
Type of electrical connection 2:	Screw connection
Connection position:	Sideways

Упаковка

В стандартной упаковке

Unit:	PCS
Size:	10

OOO Ensto Rus

Podsosensky per. h.20, build. 1
105 062 Moscow
Russin Federation

email: ensto.russia@ensto.com www.ensto.com
phone: +7 495 661 1039